Data Sheet



UHF Aerials – BLU HD SERIES **BLU22HD**





New version of one of the most successful aerial ranges on the market.

Superb electrical specifications with excellent directivity and gain.

Pre-assembled aerial: elements, mast mount and reflector clamp.

Fast and secure grid and dipole insertion onto the pre-assembled support.

60mm maximum mast clamp diameter and the design offers good wind loading

Main specifications

- 22 elements
- F Connector
- Impedance adaptor
- Robust design using quality materials

- Extremely quick construction
- Pre-assembled components
- Maximum mast diameter 60mm
- Impedance 75 Ohm

		BLU22HD					
Fracarro code		217905					
Elements	No.						
Band		UHF					
Channels	Europe	E21 - E69					
Technical characteristics							
Bandwidth	MHz	470 – 862					
Maximum gain	dBi	19					
Front-to-back ratio	dB	30					
Return loss	dB	-18					
Beamwidth (-3dB)	۰	+/-17					
Impedance	Ohm	75					
Mechanical characteristics							
Dimensions (L x W)	cm	242 x 50					
Maximum mast diameter	mm	60					
Wind load at 120Km/h (720N/m²)	Kg (N)	12.2 (119.56)					
Connector	Туре	F					



Data Sheet



	BLU22HD
Accessories	
Horizontal polarisation	Included
Horizontal polarisation with tilt adj.	Included
Vertical polarisation	Included
Vertical polarisation with tilt adj.	Included
Auxiliary boom	Included

Fracarro code	Item	Packaging	Quantity	Dimensions	Unit weight	Total weight
			Pcs	mm	Kg	Kg
217905	BLU22HD	Box	1	1250 x 380 x 90	3.61	-

