

Compact Msw 17 IN A/P TV

SWP1708TS SWP1712TS

SWP1716TS SWP1724TS

SWP1732TS



The **SWP17xxTS Serie** belongs to the **compact** multiswitch range with **17 inputs** (16 satellite polarities and TV); it was designed to fulfil every installation requirement in small and medium distribution systems.

The product ensures high quality in a **compact size**, its inputs are distinguished by different **colours** to make the cable connection faster and easier.


The serie is composed by 5 products: **17 inputs with 8, 12, 16, 24 and 32 output taps**; each port has a **LED** which shows the correct reception of the STB DiSEqC command.

The product can be used with **SWA1730TS** amplifier, which allows to adjust appropriately the satellite and TV gains.

Characteristics

- **Dip switch** to select **TV** gain active and passive
- **Return channel** included when TV gain is passive
- Satellite bandwidth up to **2300MHz**
- **High output level**
- **Standalone power supply** for easier installation; it provides the required voltage to the LNBS
- Easy to install thanks to **standard colour coding**
- **Low cost**
- **Compact size**

		SWP1708TS	SWP1712TS	SWP1716TS	SWP1724TS	SWP1732TS
Fracarro Code		287355	287356	287357	287358	287359
Inputs		17				
Outputs		8	12	16	24	32
Satellite						
Bandwidth	MHz	950 - 2300				
Gain	dB	0	-1	-1	-3	-4
Uptilt	dB	4				
Max Output Level (IM3)	dBμV	100				
Return Loss	dB	10				
Terrestrial						
Bandwidth	MHz	50 - 862				
Gain Active	dB	0	-1	-2	-3	-5
Gain Passive	dB	-20	-21	-22	-23	-25
Max Output Level (IM3)	dBμV	95				
Return Loss	dB	10				
General Parameters						
Isolation SAT/SAT TV/SAT	dB	30				
Standard	V, KHz	14/18 0/22 - DiSEqC 2.0				
Tap Consumption	mA	50				
DC Plug	mm	2.1x5.5x12				
	pol	internal positive, external negative				
Max current to LNB	mA	4000				
Dimensions	mm	120x310x40	190x310x40	190x310x40	260x310x40	310x310x40
Operating Temperature	°C	-20 ÷ 60				

		PSU1340TS				
Fracarro Code		287376				
Output Voltage	V	13				
Output Current	mA	4000				
Main Voltage	V, Hz	120-240, 50-60				
Isolation	Classe	II				
DC Plug	mm	2.1x5.5x12				
	pol	 internal positive, external negative				
Dimensions	mm	110 x 52 x 34				
Operating Temperature	°C	0 ÷ 40				

Code	Item	Packaging	Quantity	Dimensions	Net Weight	Weight
			pcs	Mm	kg	kg
287355	SWP1708TS	Single	1	330x245x55	1	1
287356	SWP1712TS	Single	1	330x245x55	1.3	1.3
287357	SWP1716TS	Single	1	330x245x55	1.3	1.3
287358	SWP1724TS	Single	1	390x255x55	1.6	1.6
287359	SWP1732TS	Single	1	385x315x45	1.7	1.7
287376	PSU1340TS	Single	1	130x80x60	0.3	0.3

Installation Example

